


NEPTUNE 125C High Temp

HIGH TEMPERATURE WATER HOSE



Product Information

Order Ref:	HWH-SIZE mm
Tube:	EPDM CONDUCTIVE RUBBER
Reinforcement:	HIGH TENSILE SYNTHETIC TEXTILE AND STEEL WIRE HELIX
Cover:	ABRASION, HEAT, OZONE AND WEATHER RESISTANT, SMOOTH CONDUCTIVE EPDM RUBBER
Application:	FOR SUCTION AND DELIVERY OF HOT WATER WITH VERY LIGHT CHEMICAL CONTENT IN INDUSTRIAL AND AUTOMOTIVE APPLICATIONS
Specification:	ISO 1307

										
inch	mm	mm	BAR	PSI	BAR	PSI	BAR	mm	gr/m	m
1	25	35	10	150	30	435	-0.92	95	590	61
2	51	62	10	150	30	435	-0.92	215	1360	61
3	76	88	10	150	30	435	-0.92	350	2270	61
4	102	116	10	150	30	435	-0.92	490	3380	61
6	150	168	10	150	30	435	-0.8	760	6090	30

-40°C to + 125°C

Branding: GENERAL PURPOSE EPDM S&D 10 BAR (150 PSI) ?
Colour : BLACK

We use cookies to give you the best experience on our site. By using our site you accept our [Privacy Policy](#)[Accept & Close](#)