








HILCOFLEX

Rubber Covered Multipurpose Hose



Product Information

Order Ref:	HIL-SIZE-MM
Tube:	SMOOTH FOR MINIMUM FRICTION LOSS
Reinforcement:	HIGH TENACITY POLYESTER WARP AND POLYAMIDE/POLYESTER WEFT GIVING HIGH TENSILE STRENGTH
Cover:	HIGH GRADE FORMULATION NBR/PVC COMPOUND EXTRUDED IN ONE-STEP PRODUCTION PROCESS, RIBBED FOR ABRASION RESISTANCE
Application:	FOR CONSTRUCTION SITES, AGRICULTURE, MINING, WATER TRANSFER AND COMPRESSED AIR. FOR IRRIGATION, LIGHTWEIGHT SEWER CLEANING AND CABLE COVER PROTECTION

	 ID	WALL THICKNESS	 WP	 WP	 BP	BREAKING STRENGTH	 W/A	 COL
inch	mm	mm	BAR / PSI	MAXIMUM BAR / PSI	BAR / PSI	KG	gr/mt	mtr
2	52	2.5	16 / 230	20 / 290	50 / 725	3.9	400	100
2 1/2	65	2.5	16 / 230	20 / 290	50 / 725	4.3	540	100
3	76	2.9	16 / 230	20 / 290	50 / 725	6.5	650	100
4	102	3.3	16 / 230	20 / 290	50 / 725	9.5	1000	100
5	127	3.5	14 / 205	17 / 245	42 / 610	17	1400	100
6	152	3.7	14 / 205	17 / 245	42 / 610	17.9	1800	100
8	203	3.9	10 / 145	12 / 175	30 / 435	26.9	2600	100



-20°C to +80°C

Branding: NONE
Colour : BLACK

We use cookies to give you the best experience on our site. By using our site you accept our [Privacy Policy](#) [Accept & Close](#)