







VACUUM

INDUSTRIAL VACUUM CLEANER HOSE



Product Information

| | |
|----------------|---|
| Order Ref: | VAC-SIZE-MM & CUFF-SIZE-MM |
| Tube: | OPEN PROFILE GEOMETRY EVA WALL |
| Reinforcement: | SELF SUPPORTING PROFILE DESIGN, CRUSH RESISTANT |
| Cover: | SURFACE RESISTANCE 10 ¹¹ ? RESISTANT TO ALKALIS AND ACIDS, RESISTANCE TO CHEMICALS, UV AND OZONE - LIGHTWEIGHT, FLOATABLE, CRUSH RESISTANT GAS AND LIQUID TIGHT |
| Application: | FOR INDUSTRIAL VACUUM CLEANERS - EXTRACTION AND CONVEYANCE IN EXPLOSION HAZARD AREAS, ELECTROSTATIC DISCHARGING / ANTISTATIC / ELECTRICALLY CONDUCTIVE HOSE ALSO FOR USE FOR SWIMMING POOL CLEANING |

| | | | | | | |
|-------|---|---|---|--|---|---|
| |  |  |  |  |  |  |
| inch | mm | mm | BAR | mm | gr/m | m |
| 1 1/4 | 32 | 40 | 0.5 | 66 | 240 | 15* |
| 1 1/2 | 38 | 47 | 0.5 | 74 | 310 | 15* |
| 2 | 51 | 60 | 0.5 | 97 | 440 | 15* |

30 Mtr coils also available to order

NB: THIS IS ANTISTATIC SUCTION HOSE, EVA ELECTRICALLY CONDUCTIVE 10¹¹?, CRUSH RESISTANT, LIGHTWEIGHT

| CUFFS mm | CUFF Length mm | Threading depth Hose mm | Total Lengthmm | Weight gr/m | Suitable for Hose I.D. mm |
|----------|----------------|-------------------------|----------------|-------------|---------------------------|
| 32 | 44 | 40 | 85 | 60 | 32 |
| 38 | 44 | 40 | 85 | 70 | 38 |
| 51 | 49 | 41 | 90 | 90 | 51 |

NB: THESE ARE ELECTRICALLY CONDUCTIVE 10?? Colour Black



-25°C TO +65°C

Branding: NONE
Colour : BLACK

We use cookies to give you the best experience on our site. By using our site you accept our [Privacy Policy](#) [Accept & Close](#)