





FIRE LAYFLAT TYPE 2

LAYFLAT FIRE FIGHTING HOSE TYPE 2



Product Information

Order Ref:	TYPE 2-SIZE MM
Tube:	HIGH GRADE EPDM RUBBER - FLEXIBLE AT LOW PRESSURE & SUITABLE FOR HOT WATER. GOOD RESISTANCE - SEA WATER, CHEMICALS, OZONE
Cover:	HIGHLY ABRASION RESISTANT COATING FOR RESISTANCE TO HEAT, OIL AND CHEMICALS
Application:	FIRE BRIGADES, INDUSTRY, MILITARY AND CONSTRUCTION
Specification:	ACC TO DIN 14811 & BS6391 TYPE 2 - only applies to the hose (medium water 20°C)

	 ID	 BP	 W/A	Wall Thickness	 COL
inch	mm	BAR	gr/m	mm	m
1 1/2	38	60	235	2,10	60
	40	60	255	2,10	60
1 3/4	45	60	290	2,10	60
2	52	60	325	2,10	60
2 1/2	65	60	450	2,20	60
2 3/4	70	60	500	2,20	60
3	75	60	540	2,20	60

Standard colour Red, others available. Hose can be supplied with Couplings

Standard lengths 60m others available on request



-40°C to +80°C

Branding: NONE

Colour : RED

We use cookies to give you the best experience on our site. By using our site you accept our [Privacy Policy](#) [Accept & Close](#)