


SUPERFLEX PVC

PVC VACUUM DUCTING



Product Information

Order Ref:	SPF-SIZE-MM
Tube:	ENCAPSULATED AXIAL AND HELICAL RE-INFORCING YARNS
Reinforcement:	SPRING STEEL HELIX
Cover:	PLASTICISED PVC, FLEXIBLE, SMOOTH BORE DUCTING. ROBUST AND EASY TO HANDLE. GOOD ABRASION RESISTANCE
Application:	AIR HANDLING, DUST AND FUME EXTRACTION. PARTICULARLY SUITABLE FOR DOMESTIC AND INDUSTRIAL VACUUM CLEANERS

	 ID	 WP	 VACUUM	 BR	 W/A	 coil
inch	mm	BAR	BAR	mm	gr/m	m
1	25	1.05	0.91	25	220	15
11/4	32	1.00	0.91	32	270	15
11/2	38	0.95	0.80	38	370	15
	41	0.95	0.75	41	400	15
13/4	44	0.90	0.70	44	430	15
2	51	0.90	0.59	51	470	15
21/2	64	0.80	0.43	64	610	15
23/4	70	0.75	0.40	70	770	15
3	76	0.95	0.50	76	850	15
31/4	80	0.95	0.45	80	900	15

 -5°C TO +80°C in a 20°C ambient Colour : BLACK AND WHITE

We use cookies to give you the best experience on our site. By using our site you accept our [Privacy Policy](#)[Accept & Close](#)