









# TEXAS 20

20 BAR OIL SUCTION & DELIVERY HOSE



## Product Information

Order Ref:	OSH-SIZE-20 BAR
Tube:	NBR, BLACK, SMOOTH, ELECTRICALLY CONDUCTIVE
Reinforcement:	TEXTILE WRAPPED, ZINC PLATED STEEL WIRE HELIX, 2 CROSSED COPPER WIRES
Cover:	SBR/EPDM BLACK, ABRASION RESISTANT, OZONE RESISTANT, OIL RESISTANT
Application:	FOR SUCTION & DELIVERY IN OIL RELATED APPLICATIONS WITH AN AROMATIC CONTENT OF MAX 50% SUITABLE FOR INDUSTRIAL OILS, DIESEL OILS, FUEL OILS AND MINERAL OIL-BASED HYDRAULIC OILS
Specification:	SAE J517

	 ID	 OD	 WP	 BP	 VACUUM	 BR	 W/A	 COIL
inch	mm	mm	BAR	BAR	BAR	mm	gr/m	m
2	51	65	20	60	-0.92	265	2035	30
3	76	92	20	60	-0.92	400	3385	30
4	102	119	20	60	-0.92	535	4490	30
6	152	176	20	60	-0.92	840	9220	30
8	203	235	20	60	-0.92	1020	16935	30



-30°C to +70°C

Branding: TEXAS 20 - OIL SUCTION & DELIVERY - W.P. 20 BAR  
Colour : BLACK

We use cookies to give you the best experience on our site. By using our site you accept our [Privacy Policy](#) [Accept & Close](#)